

OTDR Report (1310 nm (9 μm))

General Information

File name:	22_1310.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	3:57 PM	Fiber ID:	22
Cable ID:	FAR5 to SS6A (C) A (A-B)		
Job ID:	0500831		
Comments:	END TO END TEST		


Locations

	Location A	Location B
Location	FAR5	SS6A
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

Results

Span length:	1.1474 km	Average loss:	0.651 dB/km	Injection level:	25.4 dB
Span loss:	0.747 dB	Average splice loss:	---		
Span ORL:	39.43 dB	Maximum splice loss:	---		

Graph



Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.834 dB/km	A-B average loss:	-13.914 dB/km
a	0.0000	25.411	A-B LSA loss:	0.959 dB	4-point Event Loss:	-16.407 dB
A	0.0000	25.411	A-B ORL:	37.67 dB	Maximum reflectance:	-41.5 dB
B	1.1502	41.416				
b	1.1502	41.416				

OTDR Report (1310 nm (9 μm))

Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-43.7		0.000
Section		1.0564	0.364		0.345	0.364
Reflective	2	1.0564	0.366	-55.5		0.731
Section		0.0910	0.017		0.182	0.747
Reflective	3	1.1474	---	> -23.8		0.747

Macrobend

Position (km)	Delta Loss (dB)

Pass/Fail Thresholds

	1310 nm (9 μm)

Test Parameters

	A → B
Wavelength (nm)	1310 nm (9 μm)
Range (km)	1.3000
Pulse (ns)	100
Duration (s)	5

Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.467700		
Backscatter (dB)	-79.45		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		

OTDR Report (1550 nm (9 μm))

General Information

File name:	22_1550.trc	Customer:	ADNOC
Test date:	14-Feb-24	Company:	PAN ARABIA
Test time:	3:57 PM	Fiber ID:	22
Cable ID:	FAR5 to SS6A (C) A (A-B)		
Job ID:	0500831		
Comments:	END TO END TEST		


Locations

	Location A	Location B
Location	FAR5	SS6A
Operator	PANDA	HABEEB
Model	MAX-720C-Q1-EA-EI	
Serial number	1206159	
Calibration date	29-Mar-23 (UTC)	

Results

Span length:	1.1472 km	Average loss:	0.446 dB/km	Injection level:	24.2 dB
Span loss:	0.511 dB	Average splice loss:	---		
Span ORL:	41.61 dB	Maximum splice loss:	---		

Graph



Markers

Marker	Position (km)	Value (dB)	A-B LSA attenuation:	0.713 dB/km	A-B average loss:	-14.690 dB/km
a	0.0000	24.680	A-B LSA loss:	0.820 dB	4-point Event Loss:	-17.128 dB
A	0.0000	24.680	A-B ORL:	<37.52 dB	Maximum reflectance:	> -27.4 dB
B	1.1502	41.577				
b	1.1502	41.577				

OTDR Report (1550 nm (9 μm))

Event Table

Type	No.	Pos./Length (km)	Loss (dB)	Reflectance (dB)	Attenuation (dB/km)	Cumulative (dB)
First Connector	1	0.0000	---	-43.7		0.000
Section		1.0566	0.199		0.188	0.199
Reflective	2	1.0566	0.300	-56.2		0.499
Section		0.0906	0.013		0.138	0.511
Reflective	3	1.1472	---	> -24.2		0.511

Macrobend

Position (km)	Delta Loss (dB)

Pass/Fail Thresholds

	1550 nm (9 μm)

Test Parameters

	A → B
Wavelength (nm)	1550 nm (9 μm)
Range (km)	1.3000
Pulse (ns)	100
Duration (s)	5

Test Settings

	A → B	Macrobend Wavelengths	Macrobend Delta Loss (dB)
IOR	1.468325		
Backscatter (dB)	-81.87		
Helix factor (%)	0.00		
Splice loss detection threshold (dB)	0.020		
Reflectance detection threshold (dB)	-72.0		
End-of-fiber detection threshold (dB)	5.000		